## **ESAB Cutmaster 100**

## Heavy Industrial





The ESAB Cutmaster 100 weighs in at 28 kg and provides 100 amps of cutting power. This unit's light weight compact design makes it the most portable and powerful cutting machine available. This unit combined with the 1Torch® has a maximum cut capacity of 45 mm (1 3/4"). More cut capacity than any other system in its class! Packages include power source, SL100 1Torch, spare parts kit, air filter/regulator, work cable and clamp and power cable.

- True Cut<sup>TM</sup> 35mm (1-3/8")
- Quick Disconnect Torch for easy maintenance or machine torch conversion
- Auto-Restrike on mesh or expanded metal for maximum productivity
- True-Guard<sup>TM</sup> roll bar for ultimate protection
- TD Surelok® technology for better quality cuts and longer parts life

Image text

## Industry

- Heavy Fabrication
- Ship Building
- Construction
- Manufacturing
- Structural Steel
- Rental Fleets
- Pipe and Pipelines
- Mining



| Specifications / Technical data |                       |
|---------------------------------|-----------------------|
| Recommended Cut                 | 35mm                  |
| Maximum Cut                     | 45mm                  |
| Pierce Rating                   | 20mm                  |
| Max Amperage Output             | 100A                  |
| Output Power                    | 12 kW                 |
| Dimensions                      | 305mm x 381mm x 762mm |
| Weight                          | 28.1 kg               |
| Torch Air pressure              | 5.2 bar               |
| Torch Air consumption           | 212 l/m               |
| Input voltage                   | 400V - 3 ph, 50/60 Hz |
| Duty Cycle                      | 80% @ 100A            |
| Amperage Draw                   | 27A @ 400V, 3 ph      |

| Ordering Information –                     |             |
|--|-------------|
| Description                                | Part Number |
| ESAB Cutmaster 100 6.1m SL100 400V 3ph CE  | 0559117304  |
| ESAB Cutmaster 100 15.2m SL100 400V 3ph CE | 0559117314  |

| Ordering Information – Wear and Spare Parts |             |  |  |  |
|---|-------------|--|--|--|
| 1Torch consumables                          | Part Number |  |  |  |
| Electrode                                   | 9-8215      |  |  |  |
| Start Cartridge                             | 9-8213      |  |  |  |
| Start Cartridge – Heavy<br>Duty             | 9-8277      |  |  |  |
| Tip – Drag (60A)                            | 9-8252      |  |  |  |
| Tip – Standoff (90-100A)                    | 9-8212      |  |  |  |
| Tip – Gouging B (50-100A)                   | 9-8226      |  |  |  |
| Tip – Gouging C (60-120A)                   | 9-8227      |  |  |  |
| Tip – Gouging D (60-120A)                   | 9-8228      |  |  |  |
| Shield Cup                                  | 9-8218      |  |  |  |
| Shield Cup Max Life                         | 9-8237      |  |  |  |
| Shield Cap (Drag only)                      | 9-8236      |  |  |  |
| Deflector                                   | 9-8243      |  |  |  |
| Shield Cap - Gouging                        | 9-8241      |  |  |  |

| Gouging Profiles |               |          |          |         |
|------------------|---------------|----------|----------|---------|
|                  | Output Range  | Depth    | Width    | Profile |
| Tip A            | 40 Amps (MAX) | Shallow  | Narrow   |         |
| Tip B            | 50-100 Amps   | Deep     | Narrow   |         |
| Tip C            | 60-120 Amps   | Moderate | Moderate |         |
| Tip D            | 60-120 Amps   | Shallow  | Wide     |         |
| Tip E            | 120 Amps      | Moderate | Wide     |         |

Gouging profile chart for choosing the right gouging tip based on your application

| Ontions & Appassaries            |             |
|----------------------------------|-------------|
| Options & Accessories            |             |
| Description                      | Part Number |
| Spare Parts Kit (100A)           | 5-2556      |
| Circle Cutting Guide Deluxe      | 7-8910      |
| Circle Cutting Guide kit         | 7-3291      |
| Raduis roller cutting guide kit  | 7-7501      |
| Straight Line Cutting Guide      | 7-8911      |
| Stand off cutting guide 40A      | 9-8251      |
| Stand off cutting guide 60-120A  | 9-8281      |
| Trigger guard                    | 9-8420      |
| Leather Lead Covers 6.1 m        | 9-1260      |
| Leather Lead Covers 15.2 m       | 9-1280      |
| Remote Pendent Control           | 7-3460      |
| Hand Pendant Extention           | 7-7744      |
| ATC 1Torch Lead Extension 4.6 m  | 7-7544      |
| ATC 1Torch Lead Extension 7.6 m  | 7-7545      |
| ATC 1Torch Lead Extension 15.2 m | 7-7552      |
| Single Stage Air Filter Kit      | 7-7507      |
| Two Stage Air Filter             | 9-9387      |
| Multi-Purpose Cart               | 7-8888      |
| ATC ® 1Torch® SL 100 75° 6.1M    | 7-5206      |
| ATC ® 1Torch® SL 100 90° 6.1M    | 7-5263      |
|                                  |             |

Note: All Spare Parts Kits include ten (10) Tips, five (5) Electrodes and one (1) Start Cartridge.





