



FSI59

Standard	EN ISO20345:2011
Category	S3
Size Range	UK 4 - 15 EU 37 - 50
Colour	Black
Slip Resistance	SRC

FSI59: Full lace safety boot with leather upper and comfortably padded collar. Steel toe cap protection of 200 joules. Steel midsole penetration resistant to 1100 newtons. Six hexagonal metal eyelets to the ankle for secure lace fit. Energy absorbent heel up to 20 joules. Hardwearing dual density PU sole passes SRC slip resistance. Conforms to EN ISO20345 Safety Footwear Standards. Antistatic protection. Water-resistant upper.

Upper	Water-repellent action leather upper	Construction	Injection
Inner Lining	Breathable Mesh	Outsole	Dual Density PU/PU Sole
Footbed	Removable EVA footbed	Weight	700 grams
Impact Resistance	200 Joules Steel Toe Cap	Penetration Resistance	Steel Midsole - Min. 1100N

FEATURES

- ◆ Basic Resilient Safety Boot
- ◆ Water Resistant Action Leather Upper
- ◆ Moisture Wicking Breathable Mesh Lining
- ◆ Padded PU Collar
- ◆ Padded PU Tongue
- ◆ Injected PU Midsole
- ◆ Slip Resistant PU Outsole
- ◆ Removable EVA Footbed
- ◆ Antistatic
- ◆ Energy Absorbent Heel

Care Advice: To enhance the life & performance of the footwear, upper should be kept clean & dry. Dry/damp cloth or shoe polish/spray to be used as per the need. Sole to be checked and clean regularly to maintain its traction. Any obvious damage in footwear may reduce full protection and must be replaced.