

FOCUS TIG 161 DC HP PFC

**First-class mono-phase TIG DC
and MMA inverter machine
– designed for complex site
welding assignments**

The size of the Focus TIG 161 DC HP, its PFC function and HF (high frequency) ignition makes it ideal for site welding and workshop use.

- Handy and lightweight – only 9.2 kg
- Pulse function
- PFC (Power Factor Correction)
- HF (high frequency) or lift-TIG ignition



MIGATRONiC
WELDING VALUE

MIGATRONIC A/S
Aggersundvej 33
DK-9690 Fjerritslev, Denmark
Tel: +45 96 500 600
migmatronic.com

FOCUS TIG 161 DC HP PFC

FIRST-CLASS MONO-PHASE TIG DC AND MMA INVERTER MACHINE

The Focus TIG 161 DC HP, a mono-phase (230 V) inverter-based welding machine, is ideal for site welding and workshop use because of its flexibility and portability.

It is the smallest Migatronik TIG welding machine with pulse function; the pulse function ensures better control of the weld pool, in particular when used for thin sheet welding and position welding.

Using HF (high frequency) ignition or lift-TIG ignition, the machine is applicable under all operating conditions.

The Focus TIG 161 DC HP is equipped with PFC (Power Factor Correction). PFC is an electronic circuit that ensures maximum utilisation of power and minimum power

loss. It enables welding with approx. 25% higher welding current using only 16 A mains fuses.

New technology ensures a mains voltage tolerance from -40 to +10 %, which allows welding with long mains cables or with a generator as power source.

The machine is also suitable for MMA welding using all types of rutile and basic electrodes.


Focus TIG 161 DC HP comes with MIGA Super Blue tungsten electrodes. This electrode, featuring excellent ignition and reignition properties, is applicable for all types of material.

STANDARD EQUIPMENT

- 3 m earth cable
- Carrying strap
- 16 A Schuko plug

OPTIONAL EQUIPMENT

- TIG Ergo 201 torch (hose length: optional)
- Electrode holder incl. 3 m cable
- Focus welding helmet (81910900)
- Protective frame (78866004)
- Robust trolley with cylinder holder (78857031)
- Current control unit for TIG torch



The Focus TIG 161 DC HP PFC control panel



The welding machine is ideal for all types of repairs

POWER SOURCE	FOCUS TIG 161 DC PFC
Current range, A	10-160
Mains voltage *), V +/- 10%	1x230
Fuse, A	16
Duty cycle 40°C/100% TIG, A/%/V	110/100/14.4
Duty cycle 40°C/60% TIG, A/%/V	130/60/15.2
Open circuit voltage, V	95
Protection class	23S
Norm	EN/IEC60974-1, EN/IEC60974-3, EN/IEC60974-10
Dimensions (HxWxL), mm	250x180x480
Weight, kg	9.2

*) The machine enables down to -40% by reducing the max. amperage.

We reserve the right to make changes.

